

PINNACLE SERIES

Cross Cable High Peak Frame Tent



SPECIFICATIONS		Competitor Tents	CELINA Pinnacle Tents
MATERIAL	✗	16oz / 560gsm black out PVC fabric Waterproof, Flame Retardant No mold/mildew protection • No ongoing testing	 16oz / 580gsm black out PVC fabric Waterproof, Flame Retardant (NFPA-701 / CAN-ULC-S109) Anti-UV (1000 hours), Anti-Cold Crack (-22F° / -30C°) Anti-Wicking, Anti-Mildew • Full PVC test every year
TUBING	✗	6005-T5 Aluminum 0.123" (3.13mm) wall thickness Hardness: 13HW	 6061-T6 Aluminum 0.128" (3.25mm) wall thickness Hardness: 16HW
FITTINGS	✗	Thinner, lightweight aluminum Corner Fitting • 0.18" (4.46mm) wall thickness Spreader insert • Aluminum + Steel, Heavier, Rust	 Thicker, more durable aluminum Corner fitting 0.26" (6.65mm) wall thickness, Reinforced hook • Spreader insert Heavy duty aluminum
BASE PLATE ANCHOR	✗	20" Straight anchor	 24" Anchor with hook
VERTICAL TENSION	✗	Rope Weathers quickly	 1" Ratchet strap assembly
WIND KIT	✗	Optional accessories 1.5" rope tension, 24" stakes Tent at risk of collapse in poor weather	 Included with tent 2" ratchet strap assembly, 36" stakes Wind kit steadies tent against wind & rain
CORNERS	✗	Steel open S shape hook Easy to slip off No corner flaps	 Galvanized steel, closed carabiner Stronger, more stability Corner flap secures each corner
TENT TOP EDGE	✗	Rope edge Weathers quickly, loses tension	 1" webbing reinforced overlapped edge Increased durability and longevity